



**ELECTROPORATION DEVICE**TECHNICAL FIELD

The above invention relates to an electro -  
5 poration device.

BACKGROUND ART

As it is known, recent biological, microbiological  
and pharmacological applications involve introducing  
molecules into cells, which is done by introducing the  
10 molecules through the cell membranes.

The molecules may be inorganic substances (e.g.  
drugs) or organic molecules (DNA molecules for example  
are known to be introduced in cells).

In order to introduce the molecules, the so-called  
15 electroporation methods have recently been devised,  
which are based on the application of electric pulses to  
the cells in order to produce an electric field that  
permeabilizes the cell structure enabling the substances  
to penetrate the cell membrane.

20 For instance PCT patent application WO01/07583  
describes an Electro - poration device wherein an  
electrical voltage is applied to a substrate comprising  
cells and a current is flowing through the substrate.  
The above patent application also proposes to  
25 continuously detect the ratio of the current through the  
substrate to the voltage across the substrate as an

indication of the obtained degree of electroporation of the substrate.

Finally, application WO01/07583 proposes to adjust the magnitude of the applied voltage in accordance with changes in the above ratio to achieve a controlled degree of electroporation in the substrate.

However, patent application WO01/07583 does not teach how to use the information related to the above ratio in order to have useful information for controlling the voltage; in other words, WO01/07583 merely discloses the possibility of controlling the voltage based on the detection of the above ratio but does not provide any real indication for creating a working system wherein the control of the voltage is successfully performed.

#### DISCLOSURE OF INVENTION

Scope of the present invention is to provide a working electroporation device wherein the control of the voltage applied to the substrate is obtained by means of the continuous monitoring of the ratio of the current flowing through the substrate and the voltage applied to the substrate.

According to another embodiment of the present invention, the control of the voltage is obtained by simply monitoring the current.

The above scope is obtained by the present

invention as it relates to an electro poration device as described in claim 1 or 13.

#### BRIEF DESCRIPTION OF THE DRAWINGS

The invention shall be described in accordance with the attached drawings which show a non-limiting embodiment of the invention wherein:

- ◆ figure 1 shows, in a simplified manner, an electroporation device according to the present invention;
- 10 ◆ figure 2 is a flow chart of the operations performed by the electro poration device according to a first embodiment of the invention;
- 15 ◆ figure 3 illustrates a signal ratio of current to voltage based on which the control of the electroporating pulse  $S(t)$  is performed; and
- 20 ◆ figure 4 is a flow chart of the operations performed by the electro poration device according to a second embodiment of the invention.

#### BEST MODE FOR CARRYING OUT THE INVENTION

In figure 1, number 1 indicates an electro - poration device realised according to the present invention.

25 In particular, device 1 comprises of a signal generator 3 for producing a stimulating signal  $S(t)$  that

is amplified by a power amplifier 5 and applied to electrodes 6, 7 through a power switch 10. The electrodes 6,7 are coupled with a substrate 12 containing living cells C; in particular, the substrate 5 12 may comprise a portion (for instance a tissue) of a living body (plant, animal or man) or may comprise a substrate separate from the living body and contained in a recipient (for instance a culture of animal, plant, bacterial or fungal cells in vitro).

10 The application of the electroporating signal  $S(t)$  to the electrodes 6,7 causes the creation of an electric field  $E(t)$  in the substrate 12; such a field  $E(t)$  promotes, realises or enhances the permeabilization of the membranes of the cells C rendering possible the 15 introduction of molecules (organic/inorganic) through the membranes of the cells C.

Device 1 also comprises a measuring signal generator 15 coupled with a measurement block 16 co-operating with electrodes 6, 7 for the determination of 20 the instantaneous values of the current through the substrate 12, the voltage actually applied to the substrate 12, and the ratio  $GT$  of the current through to voltage applied to the substrate 12 (i.e.  $GT=i_e/v_p$ ).

Signal generator 3, measuring signal generator 15 25 and measurement block 16 are connected, through a common BUS 20, with a central processing unit 23 coupled with

interface circuits (not shown), for the communication with peripheral devices, such as a video display 25, keyboard 26 and printer 27.

Under the control of the central processing unit 23  
5 the signal generator 3 generates a signal  $S(t)$  comprising one or a series of pulses which amplitude may be regulated as described in the following. Moreover, the central processing unit 23 receives the information related to the Voltage  $V_p$  of the stimulating signal  $S(t)$   
10 applied to the electrodes 6,7 and the current  $i_e$  that flows between the electrodes 6,7 through the substrate 12. More particularly, central processing unit 23 detects the instantaneous value of the ratio  $GT$  of the current  $i_e$  flowing through the substrate 12 and the  
15 voltage  $V_p$  applied to the substrate 12, i.e.:  $GT = i_e / V_p$ . and determines the instantaneous value of the signal  $S(t)$ .

The knowledge of the above ratio  $GT$  is used for controlling stimulating signal  $S(t)$  as described in the  
20 flow chart of figure 2.

Studies and experiments of the applicant have revealed that the curve  $C_{GT}$  representing the value of ratio  $GT$  in successive instants after the application of the stimulating signal  $S(t)$  has a particular waveform  
25 that is shown, as non limiting example, in figure 3.

In the Cartesian presentation of figure 3, Y-axis

represents increasing values or ratio  $GT$  and X-axis represents successive instants after the start of the application of the stimulating signal  $S(t)$ ; the stimulating signal  $S(t)$  being applied from time  $t = 0$  on.

Curve  $C_{GT}$  (if permeabilization process is in progress) comprises a first portion  $C_{GT-I}$  decreasing from time  $t = 0$  to a time  $t = T_m$  wherein an initial minimum is reached, a second portion  $C_{GT-II}$  increasing from the time  $T_m$  wherein the minimum is reached, and a third portion  $C_{GT-III}$  increasing with a very low rate or being substantially flat.

Curve  $C_{GT}$  (if permeabilization is not achieved and permeabilization process is not in progress) comprises a first portion  $C_{GT-I}$  decreasing from time  $t = 0$  (the second portion  $C_{GT-II}$  increasing from the time  $T_m$  is absent) and a third portion  $C_{GT-III}$  decreasing with a very low rate or being substantially flat.

In particular, block 100 of figure 2 commands the generation of the stimulating signal  $S(t)$  and the application of such a signal  $S(t)$  to the substrate through electrodes 6 and 7.

Block 100 is followed by a block 110 that introduces a delay  $T_d$  so that the stimulating signal  $S(t)$  is applied for at least a predetermined period of time  $T_d$ ; such a period of time  $T_d$  having a value so

that ratio  $GT$  has time to reach and overcome its initial minimum value  $T_m$ , in particular ratio  $GT$  at the end of delay  $T_d$  is placed on the second portion  $C_{GT-II}$  of curve  $C_{GT}$ .

5       Block 110 is followed by block 120 that determines the instantaneous gradient  $dG$  (i.e. instantaneous slope) of the ratio  $GT$  after the minimum has been reached, i.e. calculates the derivative of ratio  $GT$ ,  $dG = d(GT)/d(t)$ , at the beginning of the second portion  $C_{GT-II}$ , or more  
10       practically the difference  $\Delta G = \Delta GT / \Delta T$  at  $T_m$ .

Block 120 is followed by block 130 that compares the calculated instantaneous variation  $dG$  of the ratio  $GT$  with a reference value  $dG_{ref1}$ , for instance  $dG_{ref1} = 1$ .

In particular, if the calculated instantaneous  
15       variation  $dG$  of the ratio  $GT$  is greater than the reference value  $dG_{ref1}$  (for instance  $dG > 1$ ) block 130 is followed by block 140. If the applied signal  $S(t)$  is of too small amplitude to initiate the process of permeabilization the first minimum is not reached within  
20       the predetermined time  $T_m$  and the gradient at  $T_d$  is lower than a predetermined  $dG_{ref2}$ , for instance  $dG_{ref2} = 0$ , the  $dG$  at  $T_d$  is negative ( $dG < 0$ ) and block 130 is followed by block 180, whilst if the calculated instantaneous variation  $dG$  of the ratio  $GT$  is smaller  
25       than the reference value  $dG_{ref1}$  and at the same time larger than  $dG_{ref2}$  (for instance  $0 < dG < 1$ ) block 130 is



followed by block 150.

Block 140 performs an urgent correction to the stimulating signal  $S(t)$  in order to avoid lesions, damages or irreversible alterations in substrate 12; to  
5 that regard block 140 is followed by a block 145 that decreases the amplitude (i.e. the voltage) of the stimulating signal  $S(t)$  in order to prevent deterioration in the cells C. Block 145 is then followed by block 110.

10 Block 150 calculates the average variation  $\Delta G$  of ratio  $GT$  (i.e. the slope calculated over a period of time) in a time interval that is successive to the instant  $T_m$  wherein the minimum has been reached and that has a pre-determined time width, for instance  $\Delta G =$   
15  $\Delta GT / (T_1 - T_m)$  wherein  $T_1 > T_m$ .

Block 150 is followed by a block 160 that compares the calculated average variation  $\Delta G$  of ratio  $GT$  with a reference interval of  $\Delta G$  values, for instance a reference interval having limits 0 and  $\Delta G_{obb}$ , wherein  
20  $\Delta G_{obb}$  is an expected value of the average variation  $\Delta G$  above which the corresponding pulses will lead to a too intense permeabilization of the cells and to subsequent damages to the cells.

In particular block 160 performs the following  
25 functions:

- if the calculated average variation  $\Delta G$  of ratio

GT falls within the reference interval (for instance  $0 < \Delta G < \Delta G_{obb}$ ) then block 160 is followed by a block 170;

- if the calculated average variation  $\Delta G$  of ratio  
5 GT falls outside the reference interval and it is smaller than both the limits delimiting the interval (for instance  $\Delta G < 0 < \Delta G_{obb}$ ) then block 160 is followed by a block 180; and
- if the calculated average variation  $\Delta G$  of ratio  
10 GT falls outside the reference interval and it is greater than both the limits delimiting the interval (for instance  $\Delta G > \Delta G_{obb} > 0$ ) then block 160 is followed by block 140.

Block 180 increases the voltage of the stimulating  
15 signal in order to increase the value of the electric field  $E(t)$  applied to the substrate 12; block 180 is then followed by block 110.

Block 170 increases the voltage of the stimulating signal to an objective voltage  $V_{opt}$  in order to increase  
20 the value of the electric field  $E(t)$  applied to the substrate 12 so that the value of  $\Delta G$  tends to the expected value  $\Delta G_{obb}$ .

When the objective voltage  $V_{opt}$  has been reached block 170 is followed by a block 190 that maintains the  
25 stimulating signal at the objective voltage  $V_{opt}$  for a predetermined time that is sufficient for achieving a

complete electroporation of cells C.

Finally, block 190 may be followed by a block 195 that stops the application of pulses of the stimulating signal  $S(t)$  or by a block 200 that, if needed, continues  
5 for an extra period of time the application of the stimulating signal of the same or of another value (for example, lower), depending on the molecule to be introduced.

Figure 4 shows another preferred embodiment of the  
10 present invention. The operations that have not been modified have been indicated by blocks having the same reference numbers, and different operations are indicated with new block and numbers.

More particularly, block 120 is followed by block  
15 125 that detects the minimum of the ratio  $GT$ . This operation may be realized according know techniques for instance by comparing the instantaneous gradient  $dG$  calculated with previously recorded gradients.

Block 125 is followed by block 126 that determines  
20 the time  $T_m$  at which the minimum detected by block 125 occurs.

Block 126 is followed by block 127 that compares the detected time  $T_m$  with threshold values  $T_{tmin}$  and  $T_{tmax}$ .

25 More particularly, if the detected  $T_m$  occurs before  $T_{tmin}$  ( $T_m < T_{tmin}$ ) then block 126 is followed by block

140.

If the detected  $T_m$  occurs after  $T_{tmax}$  ( $T_m > T_{tmax}$ ), then block 126 is followed by block 180.

If  $T_m$  occurs between  $T_{tmin}$  and  $T_{tmax}$ , then block  
5 126 is followed by block 150. Accordingly block 130 is eliminated.

In actual use, electrodes 6, 7 are applied to the substrate 12 (shown schematically in Figure 1) containing live cells C. As above outlined, the  
10 substrate 12 may comprise a tissue portion forming part of a live being (human, animal or plant) or may comprise a tissue or a culture of cells (animal or plant) separated from a live being or a culture of micro-organisms (bacteria or fungi, e.g. yeast).

15 Substrate 12 is also applied with a substance (organic or inorganic or biopolymeric) 30 to be introduced into the cells C. The substance 30 may be applied in a number of different ways, some of which are listed below by way of non-limiting examples:

20 . direct application of the substance to the substrate 12, e.g. by applying to the substrate a fluid containing the substance;

. indirect application of the substance, e.g. by introducing the substance into the circulatory system of  
25 the tissue portion forming the substrate; and

.injecting the substance, e.g. using needlelike

electrodes 6,7 (not shown), each having an inner conduit containing the substance to be injected into the tissue portion forming the substrate. The substance may also be injected using needles separate from the electrodes.

5       The substance 30 introduced may be inorganic or organic or biopolymeric, e.g.

- ◆ a nucleic acid;
- ◆ a DNA molecule containing regulatory sequences and sequence coding for therapeutic genes or  
10       genes of interest for biomedical or biotechnological purposes;
- ◆ an oligonucleotide, whether natural (phosphodiesters) or modified (inside the backbone of the oligonucleotide, such as  
15       phosphosulfates, or at the extremities, by addition of groups to protect the oligonucleotides from digestion of nucleases; the description of oligonucleotide modifications being non-limiting);
- 20       ◆ a protein or peptide, whether natural or genetically or chemically modified, extracted from natural sources or obtained by synthesis, or a molecule simulating the structure of a protein or peptide, whatever its structure;
- 25       ◆ a cytotoxic agent, in particular, the antibiotic bleomycin or the cisplatinum;

- ◆ a penicillin; and
- ◆ other pharmacological agents.

The substrate 12 can also be treated without the application of a substance when the purpose is to  
5 extract from the cells C a molecule (organic or inorganic or biopolymeric) contained in or produced by the cells C. In particular, the production of proteins or small organic molecules produced by genetically modified cells or genetically selected cells could be  
10 collected from the producing cells by the controlled procedure achieved by the device here described. Extraction of substances from cells C can be achieved by diffusion through the permeabilized membranes, by reverse iontophoresis or by any other active, passive or  
15 combined mechanism.

Electroporation device 1 is activated to generate one pulse or a train of pulses (block 100) that are spaced one with respect the other. Electroporation of the cells is therefore started and the ratio GT begins  
20 to fall following the first portion of curve  $C_{GT}$  (i.e.  $C_{GT-I}$ ).

Pulses are applied for a period of time (block 110) so that ratio GT reaches its minimum at the time  $T_m$ ; for instance period  $T_d$  may be 15  $\mu s$ .

25 Then to avoid damages in the cells an immediate check is performed (blocks 120 and 130) to see if, after

the minimum has been reached, curve  $C_{GT}$  has a too rapid increase ( $dG > 1$ ); in fact, a too rapid increase after the minimum is a clear indication of irreversible damages to the cells (to that regard see curve  $C_{GT}$ -  
5 ~~IRREVERSIBLE~~ shown in figure 3). In case of a detected indication of irreversible damages a corrective action is performed (blocks 140 and 145) by immediately decreasing the voltage applied thus preventing final damage to the cells. The check of blocks 120, 130 may be  
10 substituted (or integrated) by the check of blocks 126 and 127.

In case that no indication of damage is detected then the average slope of curve  $C_{GT}$  is scrutinised (block 150) to see if and how the cells are being permealized.  
15 In particular:

- if the calculated average variation  $\Delta G$  of ratio  $GT$  falls within the reference interval ( $0 < \Delta G < \Delta G_{obb}$ ) a situation of normal beginning of the process of permeabilization of the cells is  
20 detected and the process of permeabilization is normally continued by increasing the voltage (block 170) so that the value of  $\Delta G$  tends to the expected value  $\Delta G_{obb}$ ;
- if the calculated average variation  $\Delta G$  of ratio  
25  $GT$  falls outside the reference interval and it is smaller than both limits delimiting the

interval ( $\Delta G < 0 < \Delta G_{\text{obb}}$ ) no beginning of permeabilization is detected (with this regard see curve  $C_{\text{GT-NO-PERM}}$ ) and the voltage is increased (block 180) to start the process of permeabilization; and

- if the calculated average variation  $\Delta G$  of ratio  $GT$  falls outside the reference interval and it is greater than both limits delimiting the interval ( $\Delta G > \Delta G_{\text{obb}} > 0$ ) a potentially dangerous situation is detected and a corrective action is consequently performed (blocks 140 and 145).

The above operation may also be performed by using, instead of the ratio  $GT = i_e/v_p$ , any mathematical combination of current  $i_e$  and voltage  $v_p$ .

Moreover, the above operations may also be performed by using, instead of any mathematical combination of current  $i_e$  and voltage  $v_p$ , the value of the current  $i_e$ . In fact, current  $i_e$  has a shape that is very similar to the shape of ratio  $GT$  presented in figure 3 if  $V_p$  rise times is very fast and if  $V_p$  is then constant or almost constant.

In the above case all the operations disclosed with respect to blocks 100-200 directly performed on the current  $i_e$ . For instance block 120 determines the instantaneous variation  $di_e$  of current  $i_e$ , block 130 compares the instantaneous variation  $di_e$  with reference



values, block 150 calculates an average variation  $\Delta i_e$  of current  $i_e$  and block 160 compares the calculated average variation  $\Delta i_e$  with reference values.

According to the above embodiment, it is necessary  
5 a more simple equipment for measure and calculation and the electroporation device provide a stimulating signal extremely "square".

It is therefore clear that, according to the present invention, the curve  $C_{GT}$  is constantly monitored  
10 and the stimulating signal is applied in a modified manner according to the detected waveform of an initial portion of curve  $C_{GT}$ .

In particular, the application of the stimulating signal is dependent on the shape of the curve  $C_{GT}$ , in  
15 particular the slope at particular time points.

Studies and experiments performed by the applicant have revealed that controlling the process of permeabilization as above outlined, i.e. focusing the analysis in the initial part of the waveform that  
20 corresponds to the initial instants wherein the process has been started but the real permeabilization has not still occurred, permits from one side to avoid damages to the cells and from the other side to obtain a good permeabilization of the cells.

CLAIMS

1.- Electroporation device for the permeabilization of cells (C) contained in a substrate (12) comprising signal generating means (3) for generating a stimulating  
5 signal (S(t)) applied by means of electrodes (6,7) to the substrate (12) wherein an electric field (E(t)) permeabilizing the cells membranes is induced;

the device being characterized by comprising:

- means for measuring, calculating and monitoring  
10 (15,16,23) the instantaneous value of a mathematical combination (GT) of current (ie) flowing between said electrodes (6,7) and through the substrate (12) and voltage (Vp) of the stimulating signal (S(t)) applied to the  
15 substrate (12) by means of said electrodes (6,7);

said device further comprising controlling means (100-170) for applying the stimulating signal in a controlled manner according to the waveform of an  
20 initial portion of the curve  $C_{GT}$  representing the value of the mathematical combination (GT) in successive instants after the beginning of the application of the stimulating signal (S(t)).

2.- Device as claimed in claim 1, wherein said  
25 controlling means (100-170) comprise timing means (110) for applying said stimulating signal for a predetermined

period of time  $T_d$  and analysing the initial portion of the waveform of curve  $C_{GT}$  to detect a minimum value of the curve  $C_{GT}$  within the interval  $t = 0$  and  $t = T_d$ .

3.- Device as claimed in claim 1 or 2, wherein said  
5 controlling means (100-170) calculate the slope of the waveform of curve  $C_{GT}$  after that a minimum in curve  $C_{GT}$  has been reached.

4.- Device as claimed in any of the preceding  
claims, wherein said controlling means (100-170)  
10 comprise hazard detecting means (120) determining the instantaneous gradient ( $dG$ ) of said mathematical combination (GT) after a minimum has been reached in said curve  $C_{GT}$ ;

said controlling means further comprise first  
15 comparing means (130) for comparing the calculated instantaneous gradient  $dG$  with at least a reference value ( $dG_{ref1}$ ) and selecting correcting means (140,145) for performing an urgent correction to the stimulating signal  $S(t)$  in order to avoid lesions, damages or  
20 irreversible alterations in said substrate (12).

5.- Device as claimed in claim 4, wherein said correcting means (140,145) decreases the voltage of the stimulating signal  $S(t)$  in order to prevent deterioration in the cells (C).

25 6.- Device as claimed in any of the preceding claims, wherein said controlling means (100-170)

comprise slope determining means (150) calculating the average variation  $\Delta G$  of said mathematical combination (GT) in a time interval that is successive to the instant  $T_m$  wherein a minimum in the curve ( $C_{GT}$ ) has been  
5 reached and that has a pre-determined time width;

said controlling means further comprising second comparing means (160) comparing the calculated average variation  $\Delta G$  of said mathematical combination GT with a reference interval of  $\Delta G$  values.

10 7.- Device as claimed in claim 6, wherein said second comparing means (160) performs the following functions:

- if the calculated average variation  $\Delta G$  of said mathematical combination GT falls within the  
15 reference interval ( $0 < \Delta G < \Delta G_{obb}$ ) continuing means (170) are selected;
- if the calculated average variation  $\Delta G$  of said mathematical combination GT falls outside the reference interval and it is smaller than both  
20 limits delimiting the interval ( $\Delta G < 0 < \Delta G_{obb}$ ) adjusting means (180) are selected; and
- if the calculated average variation  $\Delta G$  of said mathematical combination GT falls outside the reference interval and it is greater than both  
25 limits delimiting the interval ( $\Delta G > \Delta G_{obb} > 0$ ) correcting means (140) are selected.

8.- Device as claimed in claim 7, wherein said adjusting means (180) increase the voltage of the stimulating signal in order to increase the value of the electric field  $E(t)$  applied to the substrate (12); said  
5 adjusting means (180) subsequently selecting said means for calculating and monitoring (15,16,23) the instantaneous value of the said mathematical combination (GT) and said controlling means.

9.- Device as claimed in claim 7, wherein said  
10 continuing means (170) increase the voltage of the stimulating signal to an objective voltage  $V_{opt}$  in order to increase the value of the electric field  $E(t)$  applied to the substrate (12) so that the value of said average variation  $\Delta G$  tends to an expected value  $\Delta G_{obb}$ .

15 10. - Device as claimed in any of the preceding claims, wherein said controlling means (100-170) detects (125) a minimum of said initial portion of said curve and determining (126) the time  $T_m$  at which the minimum is reached.

20 11.- Device as claimed in claim 10, wherein third comparing means (127) are provided to compare the detected time  $T_m$  with threshold values  $T_{tmin}$  and  $T_{tmax}$ ;

said third comparing means (127) performing the following operations:

25 - if the detected  $T_m$  occurs before  $T_{tmin}$  ( $T_m < T_{tmin}$ ) then correcting means (140) are selected;

- if the detected  $T_m$  occurs after  $T_{tmax}$  ( $T_m > T_{tmax}$ ), then adjusting means (180) are selected;  
and

- - if the detected  $T_m$  occurs between  $T_{tmin}$  and  
5  $T_{tmax}$ , then continuing means (170) are selected.

12.- Device as claimed in any of the proceeding claims, wherein said mathematical combination comprise the ratio  $GT$  between said current ( $i_e$ ) and said voltage ( $V_p$ ).

10 13.- Electroporation device for the permeabilization of cells (C) contained in a substrate (12) comprising signal generating means (3) for generating a stimulating signal ( $S(t)$ ) applied by means of electrodes (6,7) to the substrate (12) wherein an  
15 electric field ( $E(t)$ ) permeabilizing the cells membranes is induced;

the device being characterized by comprising:

- means for measuring, calculating and monitoring  
(15,16,23) the instantaneous value of the current ( $i_e$ )  
20 flowing between said electrodes (6,7) and through the substrate (12);

said device further comprising controlling means (100-170) for applying the stimulating signal in a controlled manner according to the waveform of an  
25 initial portion of the curve representing the value of the current ( $i_e$ ) in successive instants after the

beginning of the application of the stimulating signal  
(S(t)).

14.- Use of a device as described in any of the  
preceding claims, to extract molecules from the living  
5 cells comprised in the substrate.

15.- Use of a device as described in any of the  
preceding claims, to introduce molecules into living  
cells.

16.- Use of the device as claimed in claim 15,  
10 wherein said molecules comprise one of the following:

- ◆ a DNA or a RNA molecule containing regulatory  
sequences and sequence coding for therapeutic  
genes or genes of interest for biomedical or  
biotechnological purposes;
- 15 ◆ an oligonucleotide, (ribo- or deoxyribo-  
nucleotide, single or double strand, including  
the SiRNA), whether natural (phosphodiester) or  
modified (inside the backbone of the  
oligonucleotide, such as phosphosulfates, or at  
20 the extremities, by addition of groups to  
protect the oligonucleotides from digestion of  
nucleases;
- ◆ a protein or peptide, whether natural or  
genetically or chemically modified, extracted  
25 from natural sources or obtained by synthesis,  
or a molecule simulating the structure of a

protein or peptide, whatever its structure;

♦ a cytotoxic agent, in particular, the antibiotic  
bleomycin or the cisplatinum;

♦ a penicillin; and

5 other pharmacological agents.






Fig.1

2 / 4




Fig.2

3 / 4




Fig.3



**Fig.4**

## INTERNATIONAL SEARCH REPORT

Internationa

pplication No

CT/EP 03/05993

A. CLASSIFICATION OF SUBJECT MATTER  
IPC 7 C12N13/00 C12M3/00

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 C12N C12M

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 01 81533 A (MIR LLUIS ;IGEA SRL (IT); MIKLAVCIC DAMIJAN (SI)) 1 November 2001 (2001-11-01) abstract page 2, line 15 - line 20 ---	1-16
X	WO 01 07584 A (UNIV CALIFORNIA) 1 February 2001 (2001-02-01) abstract page 18, line 25 - line 33; figures 8A,8B ---	1-16
X	WO 01 07585 A (UNIV CALIFORNIA) 1 February 2001 (2001-02-01) abstract page 28, line 28 - line 34 page 29, line 1 - line 5 figures 8A,8B --- -/-	1-16



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

## \* Special categories of cited documents:

- \*A\* document defining the general state of the art which is not considered to be of particular relevance
- \*E\* earlier document but published on or after the international filing date
- \*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- \*O\* document referring to an oral disclosure, use, exhibition or other means
- \*P\* document published prior to the international filing date but later than the priority date claimed

\*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

\*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

\*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

\*&\* document member of the same patent family

Date of the actual completion of the international search

24 October 2003

Date of mailing of the international search report

30/10/2003

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Weijland, A

## INTERNATIONAL SEARCH REPORT

Internationa l application No

PCT/EP 03/05993

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 01 07583 A (UNIV CALIFORNIA) 1 February 2001 (2001-02-01) abstract page 29, line 13 - line 24; claims 1-4 -----	1-16

## INTERNATIONAL SEARCH REPORT

Interna Application No

PCT/EP 03/05993

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
WO 0181533	A	01-11-2001	IT T020000389 A1	22-10-2001
			AU 5872901 A	07-11-2001
			WO 0181533 A1	01-11-2001
WO 0107584	A	01-02-2001	US 6300108 B1	09-10-2001
			US 6403348 B1	11-06-2002
			AU 6231400 A	13-02-2001
			AU 6364200 A	13-02-2001
			AU 6365000 A	13-02-2001
			CA 2378110 A1	01-02-2001
			CA 2378113 A1	01-02-2001
			CA 2378147 A1	01-02-2001
			EP 1196549 A1	17-04-2002
			EP 1196550 A2	17-04-2002
			EP 1196551 A1	17-04-2002
			JP 2003505072 T	12-02-2003
			JP 2003505073 T	12-02-2003
			JP 2003520574 T	08-07-2003
			WO 0107583 A1	01-02-2001
			WO 0107584 A1	01-02-2001
			WO 0107585 A1	01-02-2001
			US 2002137121 A1	26-09-2002
			US 2003194808 A1	16-10-2003
			US 2003166181 A1	04-09-2003
			US 6482619 B1	19-11-2002
			US 6387671 B1	14-05-2002
			US 2001051366 A1	13-12-2001
			US 2001046706 A1	29-11-2001
WO 0107585	A	01-02-2001	US 6300108 B1	09-10-2001
			US 6387671 B1	14-05-2002
			AU 6231400 A	13-02-2001
			AU 6364200 A	13-02-2001
			AU 6365000 A	13-02-2001
			CA 2378110 A1	01-02-2001
			CA 2378113 A1	01-02-2001
			CA 2378147 A1	01-02-2001
			EP 1196549 A1	17-04-2002
			EP 1196550 A2	17-04-2002
			EP 1196551 A1	17-04-2002
			JP 2003505072 T	12-02-2003
			JP 2003505073 T	12-02-2003
			JP 2003520574 T	08-07-2003
			WO 0107583 A1	01-02-2001
			WO 0107584 A1	01-02-2001
			WO 0107585 A1	01-02-2001
			US 2002137121 A1	26-09-2002
			US 2003194808 A1	16-10-2003
			US 2003166181 A1	04-09-2003
			US 6403348 B1	11-06-2002
			US 6482619 B1	19-11-2002
			US 2001051366 A1	13-12-2001
			US 2001046706 A1	29-11-2001
WO 0107583	A	01-02-2001	US 6300108 B1	09-10-2001
			US 6482619 B1	19-11-2002
			AU 6231400 A	13-02-2001
			AU 6364200 A	13-02-2001

## INTERNATIONAL SEARCH REPORT

Intern:

Application No

CT/EP 03/05993

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 0107583	A	AU 6365000 A	13-02-2001
		CA 2378110 A1	01-02-2001
		CA 2378113 A1	01-02-2001
		CA 2378147 A1	01-02-2001
		EP 1196549 A1	17-04-2002
		EP 1196550 A2	17-04-2002
		EP 1196551 A1	17-04-2002
		JP 2003505072 T	12-02-2003
		JP 2003505073 T	12-02-2003
		JP 2003520574 T	08-07-2003
		WO 0107583 A1	01-02-2001
		WO 0107584 A1	01-02-2001
		WO 0107585 A1	01-02-2001
		US 2002137121 A1	26-09-2002
		US 2003194808 A1	16-10-2003
		US 2003166181 A1	04-09-2003
		US 6403348 B1	11-06-2002
		US 6387671 B1	14-05-2002
		US 2001051366 A1	13-12-2001
		US 2001046706 A1	29-11-2001

---